sales@loopglobal.com www.loopglobal.com

∞ loop

TM /-Flex+

EV charging station Level 2

Meet the best-in-class EV charging network technology for at home or on the go. The EV-Flex+[™] Level 2 charging station is the ideal EV charging solution for multi-tenant residential, commercial, retail or municipal properties.

Sleek, compact modern design

25% higher output than the standard EV-Flex Level 2 charger

Flexibly mounted on a wall, ceiling, pole or pedestal

WiFi + LTE cellular enabled for public or private networks

RFID, Smartphone App and Bluetooth user authentication

Tamper resistant; rated for indoor/outdoor use

Universal compatibility



∞ loop

EV-Flex+™ Specifications

Electrical	• 40A/9.6kW max output, 60Hz
	• 208/240 VAC, single phase input
	Hardwired, singleport
Connector	• 25 ft. charging cable (18 ft. optional)
	SAE J1772 Type 1 standard compliant
Network	• Built-in Wi-Fi (802.11 b/g/n)
Connectivity	Built-in LTE
	Built-in Ethernet port
	OCPP 1.6 Communication Protocol
Firmware	90-day, 15-minute encrypted interval data storage
	Persistent data storage upon power interruption
	 Over the Air (OTA) updates available via Loop Network™
Core	• Weatherproof, dust-tight: NEMA 4 (IP66), IK10 tamper resistant
Specifications	 Advanced all-band (125 kHz and 13.5 MHz) RFID and BLE reader
	 Integrated cable management saddle and holster
	• Operating Temperature = -30 to 50 °C / -22 to 122 °F
	 Metering Accuracy= Embedded < ± 1%
	User Interface = Configurable OLED display
	 Status Indicators = Power/Ready, Charging, Fault Wall, ceiling, pole or pedestal mounting options
	 Wain, centing, pole of pedestal mounting options Main Enclosure Dimensions = 11.14" H x 7.56" W x 3.11" D
	 Weight = 5.28 kg / 11.64 lbs
	 User access control through RFID, NFC, Bluetooth and/or QR code
	Built-in load management (NEC 625.42 compliant, UL 60730 recognized)
Certifications	UL, FCC, Energy Star
+ Standards	Open ADR 2.0b compliant
	CTEP, NTEP
Loop Network™	Web-based Charger Management System (CMS)
(Optional)	Mobile app (iOS/Android) for drivers
	Public or private network enabled
	 Flexible network billing models (Pay Per Use, Fixed, Hybrid)
	Automated billing & real-time payment resolution
Warranty	 3-year limited product warranty (parts only)
	5-year and 10-year extended warranties available
Ordering	EV-Flex+™
Cidening	Single Port Charger
	#EVS-40A-L2-001



